

NOTES:

- 1. ALL DIMENSIONS ARE MEASURED IN INCHES.
- 2. "CF" IS 6" UNLESS OTHERWISE SPECIFIED.
- 3. "W" IS 12" UNLESS OTHERWISE SPECIFIED.
- TYPES B1, B2, B3 AND C2 ARE CONSTRUCTED OF PORTLAND CEMENT CONCRETE. (CLASS 520 - C - 2500)
- 5. TYPE D2 IS CONSTRUCTED OF ASPHALT CONCRETE.
- TYPE C2 CURB SHALL BE ANCHORED WITH DOWELS AS SHOWN OR WITH EPOXY APPROVED BY THE ENGINEER.
- 7. GRADE SHALL BE MEASURED AT CURB LINE AT TOP OF CURB.
- ALL EXPOSED CORNERS ON P.C.C. CURBS AND GUTTERS TO BE ROUNDED WITH A 1\2" RADIUS.

CITY OF BURBANK	PUBLIC WORKS	DEPARTMENT
-----------------	--------------	------------

-. ~ē

REV	BY	DATE	CURB AND GUTTER - MOUNTABLE		STANDARD PLAN
			APPROVED BY: Compress Public Works Director	6-1-92	BS-101
			Public Works Director	Date	SHEET 1 OF 1